



**AE615-DL Ver. 6.8 7.2V 2.5AH Battery Back-up
 Self-Contained Emergency Power Pack**

STANDARD FEATURES

HOUSING

- Galvanized Steel housing
- Compact and low profile casing

FEATURES

- Input transformer for safety operation
- Built-in external safety fuse
- Over-charge & discharge protection
- Over-load, Short-circuit & auto reset

STANDARD

- IEC/EN61347-1
- IEC/EN61347-2-7
- CE Compliant

PACKING SPECIFICATIONS

- 1 unit per box

PRODUCT WARRANTY

- One (1) Years for Parts
- Lifetime Free Service

ELECTRICAL FEATURES

ELECTRICAL

- 220~240 VAC 50/60Hz
- LED indicator & test switch

LED COLOR INDICATORS

- Green - Charge & Power
- Yellow – Fault or Error

CHARGER

- Charging current 150mA
- Intermittent trickle charge
- Typical full charge within 24 hours

APPLICABLE LOAD

- LED Bulb Lights 16 Watts
- LED Panel lights 18 Watts

BATTERY

- UL Listed Ni-Cd 7.2V 2.5AH

PERFORMANCE

- 2 hours ± 10% (For 16W LED Tube)

Specification and Design Improvements are Subject to Change Without Prior Notice